

Product Name

LICO Decorative PVC Wall Panels

Manufacturer's Name

LICO US / LICO Swiss



November 2024

Page 1

PRODUCT DESCRIPTION

PRODUCT FEATURES

- DESCRIPTION
 - Extruded PVC wall panels, with a variety of colors and finishes.
- BASIC USES / RELATED USES
 - Can simulate different organic surfaces such as concrete and stone.
 - Direct surface application.
 - Suitable spaces for application include restaurants, hotels, churches, and historic buildings.
- PRODUCT ATTRIBUTES AND CHARACTERISTICS
 - Tongue and groove configuration for surface mounting applications.
 - Flat textures.
 - Finishes:
 - Pigmented with a variety of colors.
 - Signature Tiles - Sizes: 5mm (15 3/64-inch x 25- 27/32 inch) (382.19 x 656.43 mm) (*these are nominal dimensions, always consult with manufacture for exact dimensions*)
Signature Plus – Size 4.7mm (30-inch x 78 inch) (36-inch x 78 inch) (48-inch x 78 inch)
(30-inch x 96 inch) (36-inch x 96 inch) (48-inch x 96 inch) (*select offering, always consult manufacture for offering*)
- ENVIRONMENTAL
 - PVC site cuttings and unused pieces can be collected and recycled.
 - Product may be recycled upon final disposal.
- SELECTION CRITERIA
 - Can be glued (surface).
 - Designed for walls where an organic look is desired.
- APPLICABLE STANDARDS, RELATED REFERENCES
 - ASTM E84 - Standard Test Method for Surface Burning Characteristics of Building Materials.
 - Fire Performance: Per ASTM E 84
 - Flame spread 40, Class B

Product Name

LICO Decorative PVC Wall Panels

Manufacturer's Name

LICO US / LICO Swiss



November 2024

Page 2

PRODUCT DESCRIPTION

- ASTM E331-00(2016), Standard Test Method for Water Penetration of Exterior Windows, Skylights, Doors, and Curtain Walls by Uniform Static Air Pressure Difference
- ASTM G21 - Resistance of Synthetic Polymeric Materials to Fungi
- PACKAGING, HANDLING, PROTECTION, AND DELIVERY INSTRUCTIONS
 - Deliver materials within original cartons and take care to handle and protect against unnecessary damage such as moisture, breakage, dirt, surface soiling, etc.
 - Allow all material components to acclimate to room temperatures before installation.
- SPECIAL WARRANTY
 - Limited Warranty: Ten (10) years from product manufacturing defects.
- LIMITATIONS
 - Certain chemical solvents should be avoided, contact the manufacturer for more information.
- AVAILABILITY
 - Nationally and internationally.
- COST
 - Refer to LICO US / LICO Swiss and authorized representatives for pricing.

PRODUCT PROPERTIES

- MATERIAL, COMPOSITION, AND DESIGN
 - Material: Virgin grade, rigid, polyvinyl chloride (PVC).
 - Recommended adhesives:
 - Loctite® Power Grab® Ultimate (white formula only), Titebond® Titegrab Ultimate®, Liquid Nails® Fuze It® and Manus® 75-AM HV
- SHAPE, MASS, AND DIMENSIONS
 - Thickness:
 - Signature - 5 mm (13/64 inches)
 - Signature Plus 4.7 mm
 - Available Sizes (nominal): *Note*- certain style panels may vary from nominal dimensions; you should always contact manufacture for dimensions.
 - Signature iles - 5mm (15 3/64-inch x 25- 27/32 inch) (382.19 x 656.43 mm); *dimensions, always consult with manufacture for exact dimensions*

Product Name

LICO Decorative PVC Wall Panels

Manufacturer's Name

LICO US / LICO Swiss



November 2024

Page 3

PRODUCT DESCRIPTION

Signature Plus Panels – Size 4.7mm (30-inch x 78 inch) (36-inch x 78 inch) (48-inch x 78 inch) (30-inch x 94 inch) (36-inch x 94 inch) (48-inch x 94 inch) check *with manufacturer for color offering in XL program.*

- **FINISH, COLORS AND TEXTURES**

- Signature Standard Colors: Frost Nickel, Carrara Marble, Venetian Marble, Ashen Slate, Black Ice & Dusty Pearl,
- Signature Standard Colors: Wind Gust, Carrara Marble, Hermitage Granite, Cracked Slate, Iced Pewter & Smoky Sky
- Trims, to finish wall edges; available. Please contact the manufacturer for information.
- Shelves, benches and niches in matching colors available. Please contact the manufacturer for information.

PRODUCT PLACEMENT

- **PREPARATION WORK**

- Perform installation as late as possible in the building process after any dust-generating activities have been completed.
- Install tiles in accordance with installation instructions.

- **INSTALLATION / ERECTION**

- Cutting Panels: Using a table saw or circular saw for clean straight cuts and jig saw for irregular cuts like wall outlets.
- Surface Mounting:
 - Apply adhesive to substrate using a notched trowel. If a tube adhesive is used, repeated pressing of tiles to substrate may be required.
 - Install Trim (if used), Install full panels, working across the room.
 - Overlap tongue and groove tiles and build across the room
 - When installing in wet environments, apply bead of silicon to tongue and groove connection.
 - Once completed, firmly press all wall tiles to ensure proper adhesive bond.
- Contact manufacturer for detailed installation guide.

- **MAINTENANCE INSTRUCTIONS AND PROCEDURES**

- Clean with mild soap and water.

Product Name

LICO Decorative PVC Wall Panels

Manufacturer's Name

LICO US / LICO Swiss



November 2024

Page 4

PRODUCT DESCRIPTION

-
- Daily, moderate dust or vacuum clean with a soft, clean brush attachment. (if necessary)
 - On a weekly basis, provide manual wet cleaning. (if necessary)

Corporate Identification

LICO US / LICO Swiss
2341 Industrial Drive
Neenah, WI, U.S.A. 54956
Phone Toll Free: 1-800-434-3750
Fax Toll Free: 1-800-434-3751
Website: lico-us.com

Technical Services Available

Product available nationally and internationally or from regional representatives.

Classification and Filing

MasterFormat 1995
Section 09510 - PVC Wall Panels
MasterFormat 2004
Section 09 51 00 - PVC Wall Panels