

True Earth Floorworks™

PLASTIC-FREE • ALL NATURAL • PROFESSIONAL GRADE

Product Testing

Measure	Test	Test Result	Rating
Wear Resistance	NALFA 3.7	6,200 Cycles	Class 4 Heavy Commercial
Caster Chair Resistance	NALFA 3.9	35,000+ Cycles	Class 4 Heavy Commercial
Small Ball Impact	NALFA 3.5	> 500	Class 4 Heavy Commercial
Large Ball Impact	NALFA 3.5	> 1400	Class 4 Heavy Commercial
Xenon Light Resistance	NALFA 3.3	5	Class 4 Heavy Commercial
Thickness Swell	NALFA 3.2	7.50%	Class 4 Heavy Commercial
Surface Bond	NALFA 3.10	1.61 N/mm ²	Class 4 Heavy Commercial
Cleanability-Stain Resistance	NALFA 3.4	Total Score 4	Class 4 Heavy Commercial
Static Load	NALFA 3.1	900 lbs	Class 2 Light Commercial
Assembled Joint Swell Test	NALFA Joint Swell Test	0.000 mm	n/a
Water Swell	EN 317	< 1% after 24-hr submersion	n/a
Slip Resistance DFOC	ANSI A137.1	0.5	n/a
Sound Insulation STC, w/o ceiling	ASTM E90	53	n/a
Sound Transmission IIC, w/o ceiling	ASTM E492	59	n/a

Product Specifications

	Construction	• HydroWood Core: 9 mm Water Proof – 5 Layer Pressed • HDF Core: 9 mm Water Resistance – 5 Layer Pressed • Dryback: 4 mm Water Proof – 5 Layer Pressed
	Surface Protection	Hotcoat®
	Underlayment	100% recycled, natural cork
	Available Sizes, Quantity & s.f. per carton	HydroWood or HDF: • 7.9" x 48.6" @ 8 planks = 21.27 s.f. • 7.9" x 71.5" @ 6 planks = 23.44 s.f. • 24.4" x 36.0" @ 4 tiles = 24.43 s.f. Glue Down: • 7.9" x 48.6" @ 18 planks = 47.86 s.f. • 7.9" x 71.5" @ 13 planks = 50.80 s.f. • 24.4" x 36.0" @ 9 tiles = 54.96 s.f.
	Warranty	10-Year Commercial, Limited Lifetime Residential
	Country of Origin	Made in Switzerland
	Recycled Content	79%
	Recyclable	100%