



Maintenance Guidelines @Ease Jacuzzi Sanitizing System

FRESH FILL (start-up)

1. Add **SpaGuard Stain & Scale** (1 oz. per 100 gallons).
2. Check and balance total alkalinity (80-120ppm) Adjust as needed with **SpaGuard Total Alkalinity Increaser** or **SpaGuard pH Decreaser**.
3. Check and balance pH (7.2-7.8) Adjust as need with **SpaGuard pH Increaser** or **SpaGuard pH Decreaser**.
4. Check and balance calcium hardness levels (150-250ppm) Adjust as needed with **SpaGuard Calcium Hardness Increaser** or **Vanishing Act Calcium Remover**
5. Add **Spa Frog Jump Start** packet to the water (one packet per 600 gallons).
6. Set the **Blue @Ease Mineral Cartridge** to #7 (wide open). **This cartridge will last 4 months.**
7. The **Silver @Ease SmartChlor Cartridge will last 2-4 weeks** depending on hot tub size and number of users.

@Ease Chart Gallons Setting:

- 200-350 Gallons- Setting 4
- 351-450 Gallons- Setting 5
- 451-600 Gallons- Setting 6

PUTTING THE SYSTEM TO WORK

1. Locate @ease holder in the filter compartment and remove the holder by pulling up and away from the filter cartridge.
2. Open the arms of the holder, Mineral on bottom and smartchlor goes on top. Place the "filled" holder on the filter cartridge that does not have the plumbing grid beneath the filter.
3. Rotate the holder towards the other filter cartridge to re-install the filter cover.

REGULAR SPA CARE (WEEKLY)

1. Check and Balance Alkalinity, pH, and Calcium Hardness (Refer to Fresh Fill Steps 2, 3, and 4 for details)
2. Always maintain a minimum of 0.5 to 1.5 ppm of free chlorine. Using the @Ease test strips verify your color is the same or darker for SmartChlor. If it is lighter, your cartridge may need to increase an output setting, or it may be empty and needs to be replaced. If darker, lower the smartchlor setting by ½ a setting.

REGULAR SPA CARE

1. Shock the hot tub with **SpaGuard Spa Shock Oxidizer** when you replace the **@Ease SmartChlor Cartridge** or once per month whichever occurs first.
2. Check your filters. It is recommended to clean your filters every 4 weeks using **SpaGuard Filter Cleaner**. Best results are achieved when the filters are soaked in filter cleaner overnight. Be sure to rinse the filters thoroughly before placing them back into the hot tub. Dirty filters may cause cloudy water, low jet pressure, FLO errors in your hot tub, among other things.
3. Drain and refill your hot tub every 4 months or sooner, depending on usage.

When using the FROG @ease system, it is required to use the @ease Test Strips.

We recommend every 30 days to bring in a water sample to any Georgia Spa Company location to get your water tested to check your levels.

**PLEASE ASK AN ASSOCIATE ABOUT OUR HOME AUTO SHIP PROGRAM
TO SAVE YOU BOTH TIME & MONEY!**

ALPHARETTA • 7300 North Point Pkwy, Alpharetta, GA 30022 • (770) 932-9045
ATHENS • 1850 Epps Bridge Pkwy, Athens, GA 30606 • (706) 227-4522
AUGUSTA • 1257 Augusta West Pkwy, Augusta, GA 30909 • (706) 229-8827
BUFORD • 3480 Financial Center Way, Buford, GA 30519 • (770) 932-9061
KENNESAW • 955 Ernest W. Barrett Pkwy, Kennesaw, GA 30144 • (770) 795-8787
NEWNAN • 1068 Bullsboro Drive, Newnan, GA 30265 • (770) 755-1552
SERVICE & DISTRIBUTION • 1515 University Drive, Auburn, GA 30011 • (678) 383-2583