



**WORLD'S  
STRONGEST  
BOND™**



**PRODUCT CATALOG**



# OVER 50 YEARS OF STRENGTH.

Whether you have an important home repair, a broken part that's hard to replace or need to finish-off a one-of-a-kind creation, J-B Weld has you covered. We're sold in over 70,000 retail stores, from hardware and automotive to home, farm, craft and more. Founded in Texas in 1969, J-B Weld is the original "tougher than steel" cold weld epoxy. But we've grown and innovated to offer a complete range of strongest-in-class products to help pros and DIYers of all skill levels confidently pull off projects both big and small in their homes, garage and beyond. J-B Weld, World's Strongest Bond.™





# TWIN TUBES



Our Twin Tubes are what started it all. These two-part epoxies are some of our most versatile products. With a paste-like consistency, Twin Tubes are great at filling gaps and cracks. And once cured, they create a permanent bond and can be sanded, drilled, tapped, shaped and painted.

- OUR ORIGINAL, STRONGEST EPOXIES
- BONDING AND GAP FILLING
- MOST VERSATILE



To see our Twin Tubes in action,  
visit [jbweld.com/our-videos](http://jbweld.com/our-videos)



# TWIN TUBES PRODUCT GUIDE



TWIN TUBES	Product Attributes						Metals				Plastics			Other Materials				
	Strength	Set Time	Cure Time	Dry Color	Max Temp	Fuel Resistance	Aluminum	Copper	Iron	Steel	PVC	ABS	Flexible Plastic*	Wood	Stone/Concrete	Fiberglass	Glass	Ceramic
J-B Weld 8265S/8281	5020 PSI	4-6 hrs	15-24 hrs	Dark Grey	550° F	Best	Better	Best	Best	Best	Good	Good		Better	Best	Better		Better
KwikWeld 8276/8271	3127 PSI	6 min	4-6 hrs	Dark Grey	250° F	Good	Good	Good	Good	Good	Good	Good		Good	Better	Better		Good
MarineWeld 8272	5020 PSI	4-6 hrs	15-24 hrs	Dark Grey	550° F	Better	Best	Better	Better	Better	Better	Better		Better	Better	Best		Better
ClearWeld 8212/50240	3900 PSI	5 min	1 hr	Clear	200° F		Good	Good	Good	Good	Best	Best	Better	Best	Good	Good	Best	Best

\*Not polypropylene or polyethylene



J-B Weld  
8265S/8281



KwikWeld  
8276/8271



MarineWeld  
8272



ClearWeld  
8212/50240



# TWIN TUBES



## J-B Weld® 2 oz

J-B Weld is The Original Cold Weld™ two-part epoxy system that provides strong, lasting adhesion and gap-filling to metal and other surfaces.

**Strength:** 5020 PSI  
**Set time:** 4-6 hours  
**Cure time:** 15-24 hours  
**Cure color:** Dark Grey

Part No.	Description
8265S	2 oz

**Great for:**

- All metals
- Stone/Concrete
- Fiberglass

**Top Attributes:**

- J-B Weld's strongest epoxy
- 550° F temperature resistance
- Fuel resistant

**Good for:**

- Rigid plastic
- Wood
- Ceramic

**Primary Applications:**

High-strength repairs and crafts, along with bonding and gap filling on metals, concrete and other surfaces.



## J-B Weld® 10 oz

J-B Weld 10oz is The Original Cold Weld™ in a pro-size kit.

**Strength:** 5020 PSI  
**Set time:** 4-6 hours  
**Cure time:** 15-24 hours  
**Cure color:** Dark Grey

Part No.	Description
8281	10 oz

**Great for:**

- All metals
- Stone/Concrete
- Fiberglass

**Top Attributes:**

- J-B Weld's strongest epoxy
- 550° F temperature resistance
- Fuel resistant

**Good for:**

- Rigid plastic
- Wood
- Ceramic

**Primary Applications:**

High-strength repairs and crafts, along with bonding and gap filling on metals, concrete and other surfaces.



## KwikWeld® 2 oz

KwikWeld is the fast-setting version of The Original J-B Weld two-part epoxy system.

**Strength:** 3127 PSI  
**Set time:** 6 minutes  
**Cure time:** 4-6 hours  
**Cure color:** Dark Grey

Part No.	Description
8276	2 oz

**Great for:**

- Most metals
- Stone/Concrete
- Fiberglass

**Top Attributes:**

- Fast 6 min set time
- Strong bond on most surfaces

**Good for:**

- Rigid plastic
- Wood
- Ceramic

**Primary Applications:**

Fast bonding and gap-filling projects on metal and other substrates.

# TWIN TUBES



## KwikWeld® 10 oz

KwikWeld 10oz is the fast-setting version of J-B Weld in a pro-size kit.

**Strength:** 3127 PSI  
**Set time:** 6 minutes  
**Cure time:** 4-6 hours  
**Cure color:** Dark Grey

Part No.	Description
8271	10 oz

### Great for:

- Most metals
- Stone/Concrete
- Fiberglass

### Top Attributes:

- Fast 6 min set time
- Strong bond on most surfaces

### Good for:

- Rigid plastic
- Wood
- Ceramic

### Primary Applications:

Fast bonding and gap-filling projects on metal and other substrates.



## MarineWeld® 2 oz

MarineWeld is a specially formulated two-part epoxy system that provides strong, lasting repairs for boats and other marine equipment.

**Strength:** 5020 PSI  
**Set time:** 4-6 hours  
**Cure time:** 16-24 hours  
**Cure color:** Dark Grey

Part No.	Description
8272	2 oz

### Great for:

- Aluminum
- Other metals
- Fiberglass

### Top Attributes:

- Waterproof
- High bonding strength

### Good for:

- Rigid plastic
- Wood

### Primary Applications:

Repairs on boats, pools, plumbing, and other marine equipment.



## ClearWeld® 2 oz

ClearWeld is a quick-setting epoxy adhesive that cures clear and provides a strong bond to most surfaces.

**Strength:** 3900 PSI  
**Set time:** 5 minutes  
**Cure time:** 1 hour  
**Cure color:** Clear

Part No.	Description
8212	2 oz

### Great for:

- Glass
- Tile
- Rigid plastic

### Top Attributes:

- Cures clear
- Fast 5 min set time
- High bonding strength

### Good for:

- Ceramic
- Wood
- Most metals

### Primary Applications:

Quick-cure repairs and craft projects, along with bonding on plastic, glass and other surfaces.



# SYRINGES



J-B Weld Syringes deliver high-strength bonding in an easy-to-use applicator that dispenses the two-part adhesive in a precise 1-to-1 ratio. For convenient mixing, each product comes with a tray and stick. No other tools are necessary. Syringes are ideal for bonding and gap-filling. After curing, they can be sanded and painted.

- HIGH STRENGTH, TWO-COMPONENT ADHESIVES
- PRECISE 1-TO-1 RATIO
- EASY AND CONVENIENT TO MIX



To see our Syringes in action,  
visit [jbweld.com/our-videos](http://jbweld.com/our-videos)



# SYRINGES PRODUCT GUIDE



SYRINGES	Product Attributes						Metals				Plastics			Other Materials				
	Strength	Set Time	Cure Time	Dry Color	Max Temp	Fuel Resistance	Aluminum	Copper	Iron	Steel	PVC	ABS	Flexible Plastic*	Wood	Stone/Concrete	Fiberglass	Glass	Ceramic
ClearWeld 50112/50114	3900 PSI	5 min	1 hour	Clear	250° F		Better	Better	Better	Better	Better	Better	Better	Better	Better	Good	Best	Better
PlasticBonder 50133/ 50139	3770 PSI	15 min	30 min	Tan/Black	250° F		Good	Good	Good	Good	Best	Best	Best	Good	Good	Good		Good
J-B Weld 50165	5020 PSI	4-6 hrs	15-24 hrs	Dark Grey	550° F	Best	Best	Best	Best	Best	Good	Good		Better	Best	Best		Best
KwikWeld 50176	3127 PSI	6 min	4-6 hrs	Dark Grey	250° F	Good	Better	Better	Better	Better	Good	Good		Better	Better	Better		Better
PlasticWeld 50132	3900 PSI	5 min	1 hour	Clear	250° F		Good	Good	Good	Good	Best	Best	Better	Good	Better	Good	Better	Good
MarineWeld 50172	2350 PSI	5 min	1 hour	White	250° F		Good	Good	Good	Good	Better	Better	Best	Better	Good	Better		Good
MinuteWeld 50101	2300 PSI	1 min	1 hour	Clear	250° F		Good	Good	Good	Good	Good	Good	Good	Good	Better	Good	Good	Good
HighHeat 50197	4730 PSI	1 Hour	24 hrs (room temp) 1 hr (w/heat)	Dark Grey	550° F	Better	Better	Better	Better	Better	Good	Good			Better	Better		Better
WoodWeld 50151	3770 PSI	15 min	30 min	Tan	250° F		Good	Good	Good	Good	Good	Good	Good	Best	Good	Good		Good

\*Not polypropylene or polyethylene



ClearWeld  
50112/50114



Tan PlasticBonder  
50133



Black PlasticBonder  
50139



J-B Weld  
50165



KwikWeld  
50176



PlasticWeld  
50132



MarineWeld  
50172



MinuteWeld  
50101



HighHeat  
50197



WoodWeld  
50151



# SYRINGES



## ClearWeld 25 mL

ClearWeld is a clear-curing epoxy adhesive that sets quickly and provides strong adhesion.

**Strength:** 3900 PSI

**Set time:** 5 min

**Cure time:** 1 hour

**Cure color:** Clear

Part No.	Description
50112	25 mL

### Great for:

- Glass
- Tile
- Rigid plastics

### Top Attributes:

- Cures clear
- High strength
- Quick 5 min set time

### Good for:

- Ceramic
- Wood
- Most metals

### Primary Applications:

Invisible, high-strength bonding applications for repairs, builds, and crafts.



## ClearWeld 14 mL

ClearWeld is a clear-curing epoxy that sets quickly and provides strong adhesion. Our 14 mL syringe includes a one-time-use mixer for direct adhesive application.

**Strength:** 3900 PSI

**Set time:** 5 min

**Cure time:** 1 hour

**Cure color:** Clear

Part No.	Description
50114	14 mL

### Great for:

- Glass
- Tile
- Rigid plastics

### Top Attributes:

- Cures clear
- High strength
- Quick 5 min set time

### Good for:

- Ceramic
- Wood
- Most metals

### Primary Applications:

Invisible, high-strength bonding applications for repairs, builds, and crafts.



## PlasticBonder Tan 25 mL

PlasticBonder is a flexible, strong adhesive that provides long-lasting bonding and gap-filling solutions to most plastics.

**Strength:** 3770 PSI

**Set time:** 15 min

**Cure time:** 30 min

**Cure color:** Tan

Part No.	Description
50133	25 mL

### Great for:

- Most flexible or rigid plastics\*

\*Not polypropylene or polyethylene

### Top Attributes:

- Flexible
- High strength
- Fast 30 min cure time

### Good for:

- Fiberglass
- Metal
- Wood

### Primary Applications:

Bonding and gap-filling solutions on most plastic substrates.

# SYRINGES



## PlasticBonder Black 25 mL

PlasticBonder is a flexible, strong adhesive that provides long-lasting bonding and gap-filling solutions to most plastics.

**Strength:** 3770 PSI

**Set time:** 15 min

**Cure time:** 30 min

**Cure color:** Black

Part No.	Description
50139	25 mL

**Great for:**

- Most flexible or Rigid plastics\*

*\*Not polypropylene or polyethylene*

**Good for:**

- Fiberglass
- Metal
- Wood

**Top Attributes:**

- Flexible
- High strength
- Fast 30 min cure time

**Primary Applications:**

Bonding and gap-filling solutions on most plastic substrates.



## J-B Weld® 25 mL

J-B Weld is our Original Cold-Weld™ epoxy in an easy-to-use syringe dispenser for strong, lasting adhesion.

**Strength:** 5020 PSI

**Set time:** 4-6 hours

**Cure time:** 15-24 hours

**Cure color:** Dark Grey

Part No.	Description
50165	25 mL

**Great for:**

- All metals
- Stone/Concrete
- Fiberglass

**Good for:**

- Rigid plastic
- Wood
- Ceramic

**Top Attributes:**

- J-B Weld's strongest epoxy

**Primary Applications:**

Bonds metal together and to other surfaces with high strength.



## KwikWeld 25 mL

KwikWeld is the fast-setting version of J-B Weld in an easy-to-use dispenser.

**Strength:** 3127 PSI

**Set time:** 6 min

**Cure time:** 4-6 hours

**Cure color:** Dark Grey

Part No.	Description
50176	25 mL

**Great for:**

- Most metals
- Stone/Concrete
- Fiberglass

**Good for:**

- Rigid plastic
- Wood
- Ceramic

**Top Attributes:**

- Fast 6 minute set time
- Strong bond on most surfaces

**Primary Applications:**

Fast-bonding projects on metal and other substrates.



# SYRINGES



## PlasticWeld 25 mL

PlasticWeld is a high-strength epoxy adhesive that provides a quick-setting, bond to rigid plastics.

**Strength:** 3900 PSI

**Set time:** 5 min

**Cure time:** 1 hour

**Cure color:** Clear

### Great for:

- PVC
- ABS
- Rigid plastics

### Top Attributes:

- High bond strength
- Cures clear
- Quick 5 min set time

### Good for:

- Glass
- Tile
- Metal

### Primary Applications:

Clear bonding and gap-filling applications on PVC, ABS and other rigid or semi-rigid plastics.

Part No.	Description
50132	25 mL



## MarineWeld 25 mL

MarineWeld is an adhesive & gap filler that provides waterproof, impact and UV-resistant bonds to fiberglass, most plastics, and other surfaces.

**Strength:** 2350 PSI

**Set time:** 5 min

**Cure time:** 1 hour

**Cure color:** White

### Great for:

- Fiberglass
- Most plastics\*
- Rubber

### Top Attributes:

- Waterproof
- Flexible
- Rubber (Impact/vibration resistant)
- UV-resistant

\*Not polypropylene or polyethylene

### Good for:

- Metal
- Stone/Concrete

### Primary Applications:

Bonding and gap-filling applications for marine, pool, kitchen & bath.

Part No.	Description
50172	25 mL



## MinuteWeld 25 mL

MinuteWeld is a clear-curing epoxy adhesive that sets in 1 minute.

**Strength:** 2300 PSI

**Set time:** 1 minute

**Cure time:** 1 hour

**Cure color:** Clear

### Great for:

- Glass
- Tile
- Ceramic

### Top Attributes:

- Sets in 1 minute
- Cures clear
- No clamping

### Good for:

- Rigid plastics
- Metal
- Stone

### Primary Applications:

Fast-setting bonding & gap-filling applications on many different substrates.

Part No.	Description
50101	25 mL

# SYRINGES



## HighHeat 25 mL

HighHeat is a heat-resistant epoxy adhesive for bonding and gap-filling substrates exposed to high temperatures.

**Strength:** 4730 PSI

**Set time:** 1 hour

**Cure time:** 24 hrs (room temp) 1 hr (with heat)

**Cure color:** Dark Grey

Part No.	Description
50197	25mL

**Great for:**

- Metal
- Stone/Concrete

**Good for:**

- Fiberglass

**Top Attributes:**

- 550° F heat resistance
- Fuel resistant
- Cures in an hour with heat

**Primary Applications:**

Bonding and gap-filling on mufflers, tailpipes, radiators, and other automotive or high-heat repairs.



## WoodWeld 25 mL

WoodWeld is a no-foam adhesive for bonding and repairing exterior or interior wood.

**Strength:** 3770 PSI

**Set time:** 15 min

**Cure time:** 30 min

**Cure color:** Tan

Part No.	Description
50151	25 mL

**Great for:**

- All wood surfaces

**Good for:**

- Bonding wood to other substrates

**Top Attributes:**

- No foam
- Quick setting
- Sandable & paintable

**Primary Applications:**

Bonds wood together and to other surfaces.



# PUTTY STICKS



J-B Weld Putty Sticks put a lot of strength and versatility right in your hands. Simply mix the putty by hand until the two components are a uniform color. Then mold, shape or fill the putty into a crack, gap or hole. Once cured, the putty can be sanded, drilled, tapped and painted.

- HAND MIXABLE EPOXY PUTTY
- MOLDS TO FIT AND SHAPE ANYWHERE
- SEALS AND FILLS TO REPAIR CRACKS AND HOLES



To see our Putty Sticks in action,  
visit [jbweld.com/our-videos](http://jbweld.com/our-videos)



# PUTTY STICKS PRODUCT GUIDE



PUTTY STICKS	Product Attributes						Metals				Plastics			Other Materials			
	Strength	Set Time	Cure Time	Dry Color	Max Temp	Fuel Resistance	Aluminum	Copper	Iron	Steel	PVC	ABS	Flexible Plastic*	Wood	Stone/Concrete	Fiberglass	Ceramic
SteelStik 8267	4000 PSI	5 min	1 hour	Grey	350° F	Better	Best	Best	Best	Best	Good	Good		Good	Best	Better	Good
WaterWeld 8277	4730 PSI	25 min	1 hour	White	200° F	Good	Better	Better	Better	Better	Best	Best		Better	Better	Best	Better
KwikWood 8257/8258	2450 PSI	15-25 min	1 hour	Tan			Good	Good	Good	Good	Good	Good		Best	Good	Good	Good
PlasticWeld 8237	700 PSI	25 min	4 hours	White	200° F		Good	Good	Good	Good	Better	Better	Best	Better	Good	Good	Good
HighHeat 8297	4000 PSI	1 hour	8 hours	Grey	500° F	Better	Better	Better	Better	Better	Good	Good			Better	Better	Best
TankWeld 8217	4000 PSI	5 min	1 hour	Grey	350° F	Best	Best	Better	Better	Best	Good	Good			Better	Better	Better

\*Not polypropylene or polyethylene



SteelStik 8267



WaterWeld 8277



KwikWood 8257



KwikWood 8258



PlasticWeld 8237



HighHeat 8297



TankWeld 8217

# PUTTY STICKS



## SteelStik 3.5 In

SteelStik is a hand-mixable epoxy putty that fills gaps, seals cracks, and provides structural repair on steel and other metal surfaces.

**Strength:** 4000 PSI

**Set time:** 5 min

**Cure time:** 1 hour

**Cure color:** Grey

Part No.	Description
8267	3.5 In

### Great for:

- All metals
- Stone/Concrete

### Top Attributes:

- Waterproof up to 500 PSI
- Fuel resistant
- Fast 5 minute set time

### Good for:

- Fiberglass
- Rigid plastics

### Primary Applications:

Gap-filling, sealing, and structural repairs on plumbing, auto, home and other metal applications.



## WaterWeld 3.5 In

WaterWeld is a waterproof, hand-mixable epoxy putty that seals cracks and repairs pipes and other surfaces exposed to water.

**Strength:** 4730 PSI

**Set time:** 25 min

**Cure time:** 1 hour

**Cure color:** White

Part No.	Description
8277	3.5 In

### Great for:

- Rigid plastic
- Fiberglass

### Top Attributes:

- Waterproof up to 500 PSI
- Cures underwater

### Good for:

- All metals
- Stone/Concrete

### Primary Applications:

Sealing and structural repairs on plumbing, marine, pool, bath/shower, and other applications.



## KwikWood 3.5 In

KwikWood is a hand-mixable epoxy putty for easy wood repair, filling, and sealing.

**Strength:** 2450 PSI

**Set time:** 15-25 min

**Cure time:** 1 hour

**Cure color:** Tan

Part No.	Description
8257	3.5 In

### Great for:

- Wood gap-filling
- Sealing
- Rebuilding

### Top Attributes:

- Easy to sand
- Paintable in 1 hour
- Won't shrink or sag

### Good for:

- Wood bonding

### Primary Applications:

Filling holes and other damage in wood due to rot, insects, or other factors.



# PUTTY STICKS



## KwikWood 7 In

KwikWood is a hand-mixable epoxy putty for easy wood repair, filling, and sealing.

**Strength:** 2450 PSI

**Set time:** 15-25 min

**Cure time:** 1 hour

**Cure color:** Tan

Part No.	Description
8258	7 In

### Great for:

- Wood gap-filling
- Sealing
- Rebuilding

### Top Attributes:

- Easy to sand
- Paintable in 1 hour
- Won't shrink or sag

### Good for:

- Wood bonding

### Primary Applications:

Filling holes and other damage in wood due to rot, insects, or other factors.



## PlasticWeld 3.5 In

PlasticWeld is a hand-mixable epoxy putty that fills gaps, seals cracks and provides structural repair on most plastics.

**Strength:** 700 PSI

**Set time:** 25 min

**Cure time:** 4 hours

**Cure color:** White

Part No.	Description
8237	3.5 In

### Great for:

- Most flexible or rigid plastics\*

\*Not polypropylene or polyethylene

### Top Attributes:

- Good bond strength to most plastics
- Sandable & paintable

### Good for:

- Fiberglass
- Ceramic
- Metal

### Primary Applications:

Gap-filling and sealing on most plastic surfaces.



## HighHeat 3.5 In

HighHeat is a heat-resistant, hand-mixable epoxy putty that fills gaps and seals cracks on high-temperature surfaces.

**Strength:** 4000 PSI

**Set time:** 1 hour

**Cure time:** 8 hours

**Cure color:** Grey

Part No.	Description
8297	3.5 In

### Great for:

- Metal
- Stone/Concrete

### Top Attributes:

- 500° F heat resistance
- Fuel resistant

### Good for:

- Fiberglass
- Ceramic

### Primary Applications:

Gap-filling and structural repair on mufflers, tailpipes, and other automotive or high-heat repairs.

# PUTTY STICKS



## TankWeld 3.5 In

TankWeld is a fuel-resistant hand-mixable epoxy putty that seals and repairs metal tanks.

**Strength:** 4000 PSI  
**Set time:** 5 min  
**Cure time:** 1 hour  
**Cure color:** Grey

Part No.	Description
8217	3.5 In

### Great for:

- Metal

### Good for:

- Fiberglass
- Rigid plastics\*

\*Not polypropylene or polyethylene

### Top Attributes:

- Fuel resistant
- Fast 5 minute set time

### Primary Applications:

Sealing and repairing holes in metal tanks for water, gas and other chemicals.

# SUPERWELD



J-B Weld's SuperWeld line offers innovative high-strength super glues. They're easy to use, set quickly and are ideal for instant bonding on crafts, home and auto repairs and more.

- HIGH-STRENGTH SUPER GLUES
- VERSATILE, QUICK-BONDING SOLUTIONS



To see our SuperWeld in action,  
visit [jbweld.com/our-videos](http://jbweld.com/our-videos)





# SUPERWELD PRODUCT GUIDE



	Product Attributes			Top Benefits
	Size	Strength	Set Time	
<b>SUPERWELD</b>				
SuperWeld Light-Cure 33301	4g	2800 PSI	Instant	Fully cures instantly when exposed to included blue light
SuperWeld Professional Grade 33120	20g	3500 PSI	10 sec	Highest strength
SuperWeld Extreme 33400	15g	3000 PSI	30 sec	Thick gel, highest flexibility, impact resistance, and control
SuperWeld Brush-On 33106	6g	3100 PSI	10 sec	Brush-on for clean, controlled applications
SuperWeld 2-Pack 33102	2g	700 PSI	25 min	Low cost "value pack" of two units



SuperWeld Light-Cure  
33301



SuperWeld Professional Grade  
33120



SuperWeld Extreme  
33400



SuperWeld Brush-On  
33106



SuperWeld 2-Pack  
33102



# SUPERWELD



## SuperWeld Light-Cure 4 g

SuperWeld Light Cure is our fastest super glue, specially formulated to fully cure after just ten seconds of exposure to the built-in blue light. It will also cure like a regular super glue without using the light.

<b>Strength:</b>	2800 PSI
<b>Set time:</b>	Instant (with light)
<b>Cure time:</b>	Instant (with light)

Part No.	Description
33301	4 g

**Great for:**

- Glass
- Rigid plastics

**Good for:**

- Metal
- Wood
- Stone/Concrete

**Top Attributes:**

- Fully cures instantly with light
- Bonds, seals, and fills gaps
- Comes in applicator pen with light included

**Primary Applications:**  
Instant-cure bonding, gap-filling, and sealing for repairs or craft projects, especially on small or difficult surfaces.



## SuperWeld Professional Grade 20 g

SuperWeld Professional Grade is our strongest super glue that provides an instant bond in just seconds.

<b>Strength:</b>	3500 PSI
<b>Set time:</b>	10 sec
<b>Cure time:</b>	24 hours

Part No.	Description
33120	20 g

**Great for:**

- All metals
- Stone/Concrete
- Fiberglass

**Good for:**

- Rigid plastics
- Glass
- Wood

**Top Attributes:**

- Strongest super glue
- 10 second set time

**Primary Applications:**  
High-strength, quick bonding for repairs and projects on most surfaces.



## SuperWeld Extreme 15 g

SuperWeld Extreme is a super glue gel that is specially-formulated to provide a flexible, impact-resistant bond in seconds.

<b>Strength:</b>	3000 PSI
<b>Set time:</b>	30 sec
<b>Cure time:</b>	24 hours

Part No.	Description
33400	15 g

**Great for:**

- Most plastics
- Rubber
- Leather

**Good for:**

- All metals
- Stone/concrete
- Wood

**Top Attributes:**

- Flexible, impact-resistant bond
- No-drip gel formula for maximum control

**Primary Applications:**  
Bonding applications for repair and crafts that require flexibility, impact-resistance, or need to be applied on vertical surfaces.

# SUPERWELD



## SuperWeld Brush-On 6 g

SuperWeld Brush-On delivers a strong bond in just seconds and includes a handy brush for even application on surfaces.

**Strength:** 3100 PSI

**Set time:** 10 sec

**Cure time:** 24 hours

**Great for:**

- Rigid Plastics
- Metal

**Top Attributes:**

- Brush included for no-mess, controlled applications

**Good for:**

- Glass
- Wood
- Stone/Concrete

**Primary Applications:**

Clean, controlled glue applications for craft projects or repairs, especially in tight spaces.

Part No.	Description
33106	6 g



## SuperWeld 2-Pack 2 g

SuperWeld is a super glue formulated for high strength that bonds instantly.

**Strength:** 700 PSI

**Set time:** 25 min

**Cure time:** 4 hours

**Great for:**

- Rigid Plastics
- Metal

**Top Attributes:**

- 2-pack super glue tubes

**Good for:**

- Glass
- Wood
- Stone/Concrete

**Primary Applications:**

Quick-bonding for repairs and projects on most surfaces.

Part No.	Description
33102	2 g

# FIBERWELD REPAIR CASTS

J-B Weld FiberWeld repair casts combine high-strength fiberglass wraps with adhesive for quick-curing repairs or structural reinforcement. They're easy to apply; just dip in water, wrap around the damaged area and secure with the supplied bandage to cure. After curing, the wraps can be sanded and painted.

- **EASY TO USE: JUST WET IT AND WRAP IT**
- **HIGH STRENGTH FOR STRUCTURAL REPAIRS AND SEALING**
- **CAN PAINT AND SAND**



To see our Repair Casts in action,  
visit [jbweld.com/our-videos](http://jbweld.com/our-videos)





# FIBERWELD REPAIR CASTS

## PRODUCT GUIDE



### Product Attributes

### Repair and Reinforce Applications

#### FIBERWELD REPAIR CASTS

**FiberWeld Permanent Repair Cast**  
38236

**FiberWeld Automotive Repair Cast**  
38237

**FiberWeld 1" Pipe Repair Cast**  
38248

**FiberWeld 2" Pipe Repair Cast**  
38260

#### Length

#### Cure Color

2" x 36"

Black

2" x 36"

Black

2" x 48"

White

2" x 48"

White

Tool handles, furniture, yard equipment, sporting & camping gear

Radiator hoses, tailpipes/mufflers, oil & transmission lines

Plumbing pipes up to 1" diameter

Plumbing pipes up to 2" diameter



**FiberWeld Permanent Repair Cast**  
38236



**FiberWeld Automotive Repair Cast**  
38237



**FiberWeld 1" Pipe Repair Cast**  
38248



**FiberWeld 2" Pipe Repair Cast**  
38260



# FIBERWELD REPAIR CASTS



## FiberWeld Permanent Repair Cast 2" x 36"

FiberWeld Permanent Repair Cast is a high-strength fiberglass wrap, permeated with a specially-formulated resin that hardens like steel in 15 minutes.

**Strength:** 1500 PSI

**Set time:** 15 min

**Cure time:** 1 hour

**Great for:**

- Wood
- Metal
- Fiberglass

**Top Attributes:**

- Works like a cast – just wet and wrap
- Cures in 15 minutes
- Sandable & paintable

**Good for:**

- Rubber
- Rigid plastics

**Primary Applications:**

Structural repairs and reinforcement on furniture, tool handles, sporting equipment, and more.

Part No.	Description
38236	2" x 36"



## FiberWeld Automotive Repair Cast 2" x 36"

FiberWeld Automotive Repair Wrap is a fiberglass wrap that hardens like steel in 15 minutes for temperature and water-resistant automotive repairs.

**Strength:** 1500 PSI

**Set time:** 15 min

**Cure time:** 1 hour

**Great for:**

- Metal
- Rubber
- Rigid plastics

**Top Attributes:**

- Works like a cast – just wet and wrap
- 400° F heat resistance
- 100 PSI water resistance

**Good for:**

- Fiberglass

**Primary Applications:**

Repairing and sealing radiator hoses, tailpipes, mufflers, and other auto/RV emergency repairs.

Part No.	Description
38237	2" x 36"



## FiberWeld 1" Pipe Repair Cast 2" x 48"

FiberWeld 1" Pipe Repair Cast is a high-strength fiberglass wrap, permeated with a specially-formulated resin to repair pipes up to 1" in diameter.

**Strength:** 1500 PSI

**Set time:** 15 min

**Cure time:** 1 hour

**Great for:**

- PVC
- Copper
- Steel

**Top Attributes:**

- Works like a cast – just wet and wrap
- Holds water pressure up to 500 PSI
- Anti-corrosive

**Good for:**

- Cast iron
- ABS

**Primary Applications:**

Repair and reinforcement for pipes up to 1" diameter.

Part No.	Description
38248	2" x 48"

# FIBERWELD REPAIR CASTS



## FiberWeld 2" Pipe Repair Cast 2" x 60"

FiberWeld 2" Pipe Repair Cast is a high-strength fiberglass wrap, permeated with a specially-formulated resin to repair pipes up to 2" in diameter.

**Strength:** 1500 PSI

**Set time:** 15 min

**Cure time:** 1 hour

### Great for:

- PVC
- Copper
- Steel

### Good for:

- Cast iron
- ABS

### Top Attributes:

- Works like a cast – just wet and wrap
- Holds water pressure up to 500 PSI
- Anti-corrosive

### Primary Applications:

Repair and reinforcement for pipes up to 2" diameter.

Part No.	Description
38260	2" x 60"

# EXHAUST REPAIR



J-B Weld Exhaust Repair pastes and adhesives are designed to seal and structurally repair almost any part of your vehicle's exhaust system. These products are specially formulated to withstand extremely high temperatures.

- RESIST HIGH TEMPERATURES
- PASTES FOR SEALING
- ADHESIVES FOR REPAIRING



To see our Exhaust Repair in action,  
visit [jbweld.com/our-videos](http://jbweld.com/our-videos)





# EXHAUST REPAIR PRODUCT GUIDE



	Product Attributes				Application	Use On
	Type	Size	Max Temp	Cure Time		
<b>EXHAUST REPAIR</b>						
<b>ExhaustWeld</b> 38572	Wrap	2" x 72"	1100° F	2 hours (no heat), 20 min (with heat)	High strength repairs, sealing and insulation on breaks, holes and cracks	Anywhere on exhaust system
<b>Tiger Patch Kit</b> 39205	Wrap	2" x 36"	600° F	20 min (with heat)	High strength sealing and insulation	Mufflers and Tailpipes
<b>Tiger Patch</b> 39206	Wrap	2" x 36"	600° F	20 min (with heat)	High strength sealing and insulation	Mufflers and Tailpipes
<b>ExtremeHeat</b> 37901	Paste	3 oz	1000° F	20 min (with heat)	Sealing cracks	Anywhere on exhaust system
<b>Exhaust System Sealant</b> 37903	Paste	3 oz	850° F	20 min (with heat)	Gap filling and seam/connector	From tailpipe to catalytic converter
<b>MufflerSeal</b> 37906/37912	Paste	6 oz/12 oz	850° F	20 min (with heat)	Sealing cracks	Mufflers and Tailpipes



ExhaustWeld  
38572



Tiger Patch Kit  
39205



Tiger Patch  
39206



ExtremeHeat  
37901



Exhaust System Sealant  
37903



MufflerSeal  
37906



MufflerSeal  
37912

# EXHAUST REPAIR



## ExhaustWeld 2" x 72"

ExhaustWeld is a high-strength fiberglass wrap containing a specially formulated resin to help it withstand high temperatures anywhere on the exhaust system.

**Temp resistance:** 1100° F

**Set time:** N/A

**Cure time:** 2 hours (no heat), 20 minutes (with heat)

### Use on:

- Any part of exhaust pipe

### Primary Applications:

- High-strength repairs, sealing and insulation on breaks, holes and cracks

Part No.	Description
38572	2" x 72"



## Tiger patch Kit 2" x 36"

J-B Weld Tiger patch Kit is a temperature-resistant epoxy combined with a fiberglass wrap that cures with heat to permanently patch holes and cracks in mufflers and tailpipes. The kit includes aluminum tape for sealing and securing.

**Temp resistance:** 600° F

**Set time:** N/A

**Cure time:** 20 minutes (with heat)

### Use on:

- Mufflers and tailpipes

### Primary Applications:

- Sealing holes and cracks

Part No.	Description
39205	2" x 36"



## Tiger patch 2" x 36"

J-B Weld Tiger patch is a temperature-resistant epoxy combined with a fiberglass wrap that cures with heat to permanently patch holes and cracks in mufflers and tailpipes.

**Temp resistance:** 600° F

**Set time:** N/A

**Cure time:** 20 minutes (with heat)

### Use on:

- Mufflers and tailpipes

### Primary Applications:

- High-strength sealing and insulation

Part No.	Description
39206	2" x 36"

# EXHAUST REPAIR



## ExtremeHeat 3 oz

ExtremeHeat is a steel-reinforced paste formulated to seal cracks on metal in high-temperature environments.

**Temp resistance:** 1000° F

**Set time:** 1 hour

**Cure time:** 24 hours

**Use on:**

- Any part of exhaust pipe

**Primary Applications:**

- Sealing cracks

Part No.	Description
37901	3 oz



## Exhaust System Sealant 3 oz

Exhaust System Sealant is a heat-resistant paste that seals and fills gaps on exhaust systems and pipe connections.

**Temp resistance:** 850° F

**Set time:** 30 min

**Cure time:** 2 hours

**Use on:**

- From tailpipe to catalytic converter

**Primary Applications:**

- Gap-filling and seam/connector sealing

Part No.	Description
37903	3 oz



## MufflerSeal 6 oz

MufflerSeal is a sealing paste formulated to resist heat on mufflers and tailpipes.

**Temp resistance:** 850° F

**Set time:** 30 min

**Cure time:** 2 hours

**Use on:**

- Mufflers and tailpipes

**Primary Applications:**

- Sealing cracks

Part No.	Description
37906	6 oz



# EXHAUST REPAIR



## MufflerSeal 12 oz

MufflerSeal is a sealing paste formulated to resist heat on mufflers and tailpipes.

**Temp resistance:** 850° F

**Set time:** 30 min

**Cure time:** 2 hours

### Use on:

- Mufflers and tailpipes

### Primary Applications:

- Sealing cracks

Part No.	Description
37912	12 oz

# SILICONE SEALANTS



J-B Weld Silicone Gasket Makers and Sealants resist high temperatures, oil and water to provide long-lasting solutions for automotive and home repair.

- GASKET MAKERS AND SEALANTS
- GREAT ADHESION AND FLEXIBILITY
- 100% SILICONE — NON-SHRINKING



# SILICONES PRODUCT GUIDE



SILICONES	Product Attributes			Applications
		Sensor Safe?	Max Temp	
Ultimate Grey 32327/32927	3oz/10.3oz	Yes	700° F	Intake manifolds, transmission pans, oil pans
Ultimate Black 32329/32929	3oz/10.3oz	Yes	700° F	Intake manifolds, transmission pans, oil pans
Ultimate Copper 32325	3oz	Yes	750° F	Manifolds, thermostat housing, valve covers
Hi-Temp Red 31314/31914	3oz/10.3oz	No	650° F	Manifolds, thermostat housing, valve covers
Black 31319	3oz	No	400° F	Oil pans, interior trim, lens housing
Blue 31316	3oz	No	400° F	Oil pans, transmissions, water pumps
Clear 31310	3oz	No	400° F	Sealing and caulking of baths, showers and windows
White 31312	3oz	No	400° F	Sealing and caulking of trim, moldings, sinks, and windows



Ultimate Grey  
32327



Ultimate Grey  
32927



Ultimate Black  
32329



Ultimate Black  
32929



Ultimate Copper  
32325



Hi-Temp Red  
31314



Hi-Temp Red  
31914



Black  
31319



Blue  
31316



Clear  
31310



White  
31312



# SILICONES



## Ultimate Grey 3 oz

### Top Attributes:

- High-torque load applications
- High-temperature resistant up to 700° F
- Sensor safe

### Primary Applications:

- Intake manifolds
- Transmission pans
- Oil pans

Part No.	Description
32327	3 oz



## Ultimate Grey 10.3 oz

### Top Attributes:

- High-torque load applications
- High-temperature resistant up to 700° F
- Sensor safe

### Primary Applications:

- Intake manifolds
- Transmission pans
- Oil pans

Part No.	Description
32927	10.3 oz



## Ultimate Black 3 oz

### Top Attributes:

- Maximum oil resistance
- High flexibility
- Sensor safe

### Primary Applications:

- Oil pans,
- Valve covers
- Transmission Pans

Part No.	Description
32329	3 oz



## Ultimate Black 10.3 oz

### Top Attributes:

- Maximum oil resistance
- High flexibility
- Sensor safe

### Primary Applications:

- Oil pans
- Valve covers
- Transmission pans

Part No.	Description
32929	10.3 oz

# SILICONES



## Ultimate Copper 3 oz

### Top Attributes:

- High-temperature resistant up to 700° F
- Sensor safe

### Primary Applications:

- Manifolds
- Thermostat housing
- Valve covers

Part No.	Description
32325	3 oz



## Hi-Temp Red 3 oz

### Top Attributes:

- High-temperature resistant up to 650° F

### Primary Applications:

- Manifolds
- Thermostat housing
- Valve covers

Part No.	Description
31314	3 oz



## Hi-Temp Red 10.3 oz

### Top Attributes:

- High-temperature resistant up to 650° F

### Primary Applications:

- Manifolds
- Thermostat housing
- Valve covers

Part No.	Description
31914	10.3 oz



## Black 3 oz

### Top Attributes:

- High flexibility
- Waterproof
- Temperature Resistant up to 650° F

### Primary Applications:

- Oil pans
- Interior Trim
- Lens housing

Part No.	Description
31319	3 oz

# SILICONES



## Blue 3 oz

### Top Attributes:

- Waterproof
- Non-shrinking
- Flexible

### Primary Applications:

- Oil pans
- Transmissions
- Water pumps

Part No.	Description
31316	3 oz



## Clear 3 oz

### Top Attributes:

- Waterproof
- Non-shrinking
- Flexible

### Primary Applications:

- Sealing and caulking of baths, showers and windows

Part No.	Description
31310	3 oz



## White 3 oz

### Top Attributes:

- Waterproof
- Non-shrinking
- Flexible

### Primary Applications:

- Sealing and caulking of trim, moldings, sinks, and windows

Part No.	Description
31312	3 oz



# WOOD RESTORE



J-B Weld's line of Wood Restore products are a complete solution for wood repair, restoration and other projects. Beginning with our Liquid Hardener and finishing with our polyester Repair Putties or Premium Epoxy Putties, customers can feel confident in a job well done.

- RESTORES ROTTED WOOD TO ORIGINAL STRENGTH
- EASY-TO-APPLY SEALERS AND FILLERS
- CURES FAST



To see our Wood Restore in action,  
visit [jbweld.com/our-videos](http://jbweld.com/our-videos)



# WOOD RESTORE PRODUCT GUIDE



WOOD RESTORE		
Size	Repair and Reinforce Applications	
Wood Restore Liquid Hardener 40001	16 fl oz	Quick-drying liquid for sealing and reinforcing decayed or rotted wood prior to filling with either Repair Putty or Premium Epoxy Putty
Wood Restore Repair Putty 40003/40004	0.75 Pt/ 0.8 Qt	Filling holes, cracks and damage or paint-prepping for interior and exterior wood applications
Wood Restore Premium Epoxy Putty 40006/40007	32 oz/ 64 oz	Structural repair and filling of damaged or rotted wood and other interior/exterior wood projects



Wood Restore Liquid Hardener  
40001



Wood Restore Repair Putty  
40003



Wood Restore Repair Putty  
40004



Wood Restore Premium Epoxy Putty  
40006



Wood Restore Premium Epoxy Putty  
40007

# WOOD RESTORE



## Wood Restore Liquid Hardener 16 fl oz

### Top Attributes:

- Dries in 20 min
- Easy brush-on application
- No mixing required

### Primary Applications:

- Quick-drying liquid for sealing and reinforcing decayed or rotted wood prior to filling with either Repair Putty or Premium Epoxy Putty

Part No.	Description
40001	16 fl oz



## Wood Restore Repair Putty 3/4 Pint

### Top Attributes:

- Sand and paint in 1 hour
- Great for interior or exterior wood
- Non-sagging

### Primary Applications:

- Filling holes, cracks and damage or paint-prepping for interior and exterior wood applications

Part No.	Description
40003	3/4 Pint



## Wood Restore Repair Putty 0.8 Qt

### Top Attributes:

- Sand and paint in 1 hour
- Great for interior or exterior wood
- Non-sagging

### Primary Applications:

- Filling holes, cracks and damage or paint-prepping for interior and exterior wood applications

Part No.	Description
40004	0.8 Qt



## Wood Restore Premium Epoxy Putty 32 oz

### Top Attributes:

- Adds structural strength to wood
- Won't shrink or crack
- Can be sanded, painted, drilled & tapped in 1 hour

### Primary Applications:

- Structural repair and filling of damaged or rotted wood and other interior/exterior wood projects

Part No.	Description
40006	32 oz



## Wood Restore Premium Epoxy Putty 64 oz

### Top Attributes:

- Adds structural strength to wood
- Won't shrink or crack
- Can be sanded, painted, drilled & tapped in 1 hour

### Primary Applications:

- Structural repair and filling of damaged or rotted wood and other interior/exterior wood projects

Part No.	Description
40007	64 oz



# EPOXY RESIN



J-B Weld Resin products are two-part epoxies that cure with perfect clarity for durable coatings on tabletops and bartops. They also resist scratches, sunlight, water and heat.

- CURES CLEAR FOR COATING AND CASTING
- RESISTS SCRATCHES, WATER AND HEAT
- USE FOR TABLETOPS AND ART PROJECTS



To see our Epoxy Resin in action,  
visit [jbweld.com/our-videos](http://jbweld.com/our-videos)





# EPOXY RESIN PRODUCT GUIDE



	Size	Application
<b>EPOXY RESIN</b> <b>ClearTop Tabletop Epoxy Resin</b> 41032/41128	Quart/Gallon	Crystal clear coating for tabletops and bartops
<b>UltraRez Coating and Casting Resin</b> 43032/43128	Quart/Gallon	UV resistant resin for coating tabletops and bartops, and for other resin projects like art resin, jewelry, and more



ClearTop Tabletop Epoxy Resin  
41032



ClearTop Tabletop Epoxy Resin  
41128



UltraRez Coating and Casting Resin  
43032



UltraRez Coating and Casting Resin  
43128

# EPOXY RESIN



## ClearTop Tabletop Epoxy Resin 32 fl oz

### Top Attributes:

- Cures crystal clear
- Fast 5 hour dry time
- Resists scratches, water and heat

### Primary Applications:

- Crystal clear coating for tabletops and bartops

Part No.	Description
41032	32 fl oz



## ClearTop Tabletop Epoxy Resin Gallon

### Top Attributes:

- Cures crystal clear
- Fast 5 hour dry time
- Resists scratches, water and heat

### Primary Applications:

- Crystal clear coating for tabletops and bartops

Part No.	Description
41128	Gallon



## UltraRez Coating and Casting Resin 32 fl oz

### Top Attributes:

- UV resistant
- Cures crystal clear
- Resists scratches, water, and heat

### Primary Applications:

- UV resistant resin for coating tabletops and bartops, and for other resin projects like art resin, jewelry, and more

Part No.	Description
43032	32 fl oz



## UltraRez Coating and Casting Resin Gallon

### Top Attributes:

- UV resistant
- Cures crystal clear
- Resists scratches, water, and heat

### Primary Applications:

- UV resistant resin for coating tabletops and bartops, and for other resin projects like art resin, jewelry, and more

Part No.	Description
43128	Gallon

# THREAD LOCKERS



J-B Weld Threadlockers provide a reliable and superior lock and seal for threaded fasteners on all mechanical parts, body assemblies, and hundreds of other applications to prevent loosening of fasteners from shock and vibration.

- WORKS ON SCREWS, BOLTS, AND MORE, BETWEEN 1/4" AND 1" LONG
- NO SPILLS, DRIPS, OR CLOGS
- HEAT RESISTANT UP TO 300° F





# THREADLOCKERS PRODUCT GUIDE



THREADLOCKERS		Size	Application
Perma-Lock Medium Strength Blue 24206 / 24213 / 24236		6 mL / 13 mL / 36 mL	Adhesive that locks and seals threaded fasteners, but allows for easy hand-disassembly
Perma-Lock High Strength Red 27106 / 27113 / 27136		6 mL / 13 mL / 36 mL	Adhesive that locks and seals threaded fasteners that require resistance to severe shock and vibrations



Perma-Lock  
Medium Strength Blue  
24206



Perma-Lock  
Medium Strength Blue  
24213



Perma-Lock  
Medium Strength Blue  
24236



Perma-Lock  
High Strength Red  
27106



Perma-Lock  
High Strength Red  
27113



Perma-Lock  
High Strength Red  
27136

# THREADLOCKERS



## Perma-Lock Medium Strength Blue 6 mL

### Applications:

- Adhesive that locks and seals threaded fasteners, but allows for easy hand-disassembly.

Part No.	Description
24206	6 mL



## Perma-Lock Medium Strength Blue 13 mL

### Applications:

- Adhesive that locks and seals threaded fasteners, but allows for easy hand-disassembly.

Part No.	Description
24213	13 mL



## Perma-Lock High Strength Blue 36 mL

### Applications:

- High-strength adhesive that permanently locks and seals threaded fasteners. High resistance to severe shock and vibrations. Requires special tools for disassembly.

Part No.	Description
24236	36 mL



## Perma-Lock High Strength Red 6 mL

### Applications:

- High-strength adhesive that permanently locks and seals threaded fasteners. High resistance to severe shock and vibrations. Requires special tools for disassembly.

Part No.	Description
27106	6 mL

# THREADLOCKERS



## Perma-Lock High Strength Red 13 mL

### Applications:

- High-strength adhesive that permanently locks and seals threaded fasteners. High resistance to severe shock and vibrations. Requires special tools for disassembly.

Part No.	Description
27113	13 mL



## Perma-Lock High Strength Red 36 mL

### Applications:

- High-strength adhesive that permanently locks and seals threaded fasteners. High resistance to severe shock and vibrations. Requires special tools for disassembly.

Part No.	Description
27136	36 mL



# SPECIALTY PRODUCTS



J-B Weld Specialty Repair products are designed to handle very specific fixes, from ripped leather to leaking radiators.

- APPLICATION SPECIFIC REPAIR KITS AND PRODUCTS
- ALL TOOLS INCLUDED
- SAVES TIME AND MONEY



To see our Specialty Products in action,  
visit [jbweld.com/our-videos](http://jbweld.com/our-videos).





# SPECIALTY PRODUCT GUIDE



SPECIALTY PRODUCTS	Contents	Primary Applications
<b>Windshield Saver Repair Kit 2100</b>	Repair Resin, Syringe, Applicator, Prep Items	Repairing windshield damage up to 1 1/4" diameter
<b>TankWeld Repair Kit 2110</b>	1 oz Epoxy Adhesive • 2" x 6" Fiberglass Reinforcing Cloth • Applicator	Repairing cracks and holes up to 4" in length or 1/4" in diameter on metal & aluminum gas tanks, plastic storage tanks, water tanks, and oil pans
<b>RadiatorWeld Repair Kit 2120</b>	1 oz Epoxy Adhesive • 2" x 6" Fiberglass Reinforcing Cloth • Applicator	Repairs and stops leaks on radiators made from aluminum, copper-brass, and most plastics
<b>LeatherWeld Repair Kit 2130</b>	3 oz Adhesive Paste • Fabric Backing • Colors for Matching Applicator & Texturizer	Repair tears, rips or holes up to 2" long or 1/2" wide on auto seats, car interior, furniture, clothing, boats and more
<b>MirrorWeld 33701</b>	Adhesive and Accelerator	Bonding rear view mirrors to windshields
<b>Valve Grinder 37801</b>	1.5 oz Valve Grinding Compound	Grinding and lapping compound that removes burrs, defects, and corrosion on valve faces and seats
<b>Metal Strapping Kit 37990</b>	3/4" x 60" Metal Strap • 2 Nuts and Bolts	Hanging and clamping exhaust pipes, mufflers, plumbing pipes, gutters and downspouts



Windshield Saver Repair Kit  
2100



TankWeld Repair Kit  
2110



RadiatorWeld Repair Kit  
2120



LeatherWeld Repair Kit  
2130



MirrorWeld  
33701



Valve Grinder  
37801



Metal Strapping Kit  
37990

# SPECIALTY



## Windshield Saver Repair Kit

### Contents:

- Repair Resin
- Syringe
- Applicator
- Prep Items

### Top Attributes:

- UV-cure repair system
- Prevents further spreading
- Repairs and minimizes damage

### Primary Applications:

- Repairing windshield damage up to 1 1/4" diameter

Part No.

2100



## TankWeld Repair Kit

### Contents:

- 1 oz Epoxy Adhesive
- 2" x 6" Fiberglass Reinforcing Cloth
- Applicator

### Top Attributes:

- 3100 PSI strength
- 250° F heat resistance
- Sets in 5 minutes

### Primary Applications:

- Repairing cracks and holes up to 4" in length or 1/4" in diameter on metal & aluminum gas tanks, plastic storage tanks, water tanks, and oil pans

Part No.

2110



## RadiatorWeld Repair Kit

### Contents:

- 1 oz Epoxy Adhesive
- 2" x 6" Fiberglass Reinforcing Cloth
- Applicator

### Top Attributes:

- Chemical resistant
- 250° F heat resistance
- 3100 PSI strength

### Primary Applications:

- Repairs and stops leaks on radiators made from aluminum, copper-brass, and most plastics

Part No.

2120



## LeatherWeld Repair Kit

### Contents:

- 3 oz Adhesive Paste
- Fabric Backing
- Colors for Matching
- Applicator & Texturizer

### Top Attributes:

- No heat cure or heat tools required
- Mix to match any color

### Primary Applications:

- Repair tears, rips or holes up to 2" long or 1/2" wide on auto seats, car interior, furniture, clothing, boats and more

Part No.

2130

# SPECIALTY



## MirrorWeld

### Contents:

- Adhesive and Accelerator

### Part No.

33701

### Top Attributes:

- 3000 PSI strength
- 1 Hour cure
- Resists impact, moisture, humidity, heat and vibration

### Primary Applications:

- Bonding rearview mirrors to windshields



## Valve Grinder

### Contents:

- 1.5 oz Valve Grinding Compound

### Part No.

37801

### Top Attributes:

- Auto-adjust grit for fine, smooth finish

### Primary Applications:

- Grinding and lapping compound that removes burrs, defects, and corrosion on valve faces and seats



## Metal Strapping Kit

### Contents:

- 3/4" x 60" Metal Strap
- 2 Nuts and Bolts

### Part No.

37990

### Primary Applications:

- Hanging and clamping exhaust pipes, mufflers, plumbing pipes, gutters and downspouts



# HERCULINER



Herculiner is the original do-it-yourself brush-on bed liner kit. In three easy steps a truck bed can be covered with a tough, textured polyurethane coating just like professional spray-on liners. It prevents rust and won't chip, flake or peel. Herculiner can be applied to many different types of surfaces, such as concrete, plastic, rubber, metal, wood or fiberglass.

- TOUGH, TEXTURED PAINT-ON BED LINER
- PREVENTS RUST
- WON'T CHIP, FLAKE OR PEEL



To see our Herculiner in action,  
visit [herculiner.com](http://herculiner.com)



# HERCULINER



## Herculiner Bed Liner Kit

### Contents:

- One Gallon of Herculiner Ready-to-use Protective Coating
- Application Brush for Tight Spots and Corners
- Two Rollers for Easy/Even Application
- One Roller Handle
- Abrasive Pad to Prepare Truck Bed

### Coverage

- The kit covers (1) 6ft. truck bed (Add quart for 8ft truck bed).
- Covers 55-60 sq. ft.

### Part No.

HCL1B8



## Herculiner Bed Liner Kit - Gray

### Top Attributes:

- UV protection to resist fading
- Gray color

### Contents:

- One Gallon of Herculiner Ready-to-use Protective Coating
- Application Brush for Tight Spots and Corners
- Two Rollers for Easy/Even Application
- One Roller Handle
- Abrasive Pad to Prepare Truck Bed

### Coverage

- The kit covers (1) 6ft. truck bed (Add quart for 8ft truck bed).
- Covers 55-60 sq. ft.

### Part No.

HCL1G8



## Herculiner Gallon Can

### Top Attributes:

- Provides a durable skid-resistant protective coating
- Prevents rust and won't chip, flake or peel
- Tough, textured formula with a "like new" finish

### Coverage

- Covers (1) 6ft. truck bed (Add quart for 8ft truck bed).
- Covers 55-60 sq. ft.

### Part No.

HCL1B3

# HERCULINER

## Herculiner Quart Can



### Top Attributes:

- Provides a durable skid-resistant protective coating
- Prevents rust and won't chip, flake or peel
- Tough, textured formula with a "like new" finish

### Part No.

HCL1B7

### Coverage

- Covers 12-20 sq. ft.

## Herculiner Aerosol Can



### Contents:

- Herculiner's #1 DIY liner in an easy-to-use aerosol spray, providing the same waterproof protection in the convenience of a spray-on coating.

### Part No.

HALB15

### Primary Applications:

- Great for touch-ups, cutting in before applying roll-on Herculiner, or protecting hard-to-reach areas like undercoatings and wheel wells.



