

LUMIEN™



BRASS SNAPSHOT



LUMIEN



Together, we are brighter.

Our Promise

Our Product

For almost 20 years, Lumien Lighting has been manufacturing high-quality fixtures in the lighting industry. We have made it our mission to provide the first complete modular lighting product line – our Quick Connect System by Lumien Lighting. By using our three patented modules, you can create unlimited variations of directional, area, pendant, recessed, well, catenary, and underwater fixtures. To compliment this system, Lumien Lighting also offers an integrated aluminum product line as well as a standard brass product line with removeable light sources. Our fixtures are designed and manufactured with the contractor in mind – innovation, performance, durability, and transparency are all at the forefront of Lumien Lighting's promise to the industry.

WEBSITE



Scan to visit our website

DIGITAL CATALOGS



Scan to view all of our catalogs





BRASS

LumienCORE

- 2700K & 3000K Kelvin Temperatures
- Antique Brush
- Solid Brass

LumienPRO

- Adjust color temps from 2700K – 5000K
- Select from preset color options
- Pick from preset light levels
- Antique Brush
- Solid Brass

All fixture adjustments can be made using the user-friendly LumienPRO remote (purchased separately).

AREA

Path Light Components

Path Light Caps and Stem with Adjustable Beam Spread Shroud



AREA

Path Light Components

Path Light Stem with Adjustable Beam Spread Shroud



LumienPRO
BY LUMIEN LIGHTING

A7B1-7W-A

7 Watts

245 Lumens

WW (2700K – 5000K)



LumienPRO
BY LUMIEN LIGHTING

A9B1-7W-A

7 Watts

XXX Lumens

RGBWW (2700K – 5000K)



AREA



AREA



Micro Path Light Components

Path Light Stem with Quick Connect Caps



1



LAB-043



LAB-044



LAB-045

3



Accessory,
Micro Path Light,
Standard 12" Riser
with 6' Wire Lead

ALL MODULES – ORDERED SEPARATELY

2



M4B1

Micro Module
Ordered Separately
Multiple Options Available

4



LAP-002
8" Spike

DIRECTIONAL



Brass Spot and Down Lights

IP65 Rated; Lifetime Warranty



D1B1-A

Non-Integrated
MR16 Uplight
No Lamp Included



D1B2-A

Non-Integrated
MR16 Downlight with
Single-Point Mount
No Lamp Included

DIRECTIONAL

Brass Spot and Down Lights

IP65 Rated; Lifetime Warranty



D6B1-5W-27K-A
D6B1-5W-30K-A

5 Watts
375 Lumens



D6B2-5W-27K-A
D6B2-5W-30K-A

5 Watts
350 Lumens



D6B1-10W-27K-A
D6B1-10W-30K-A

10 Watts
600 Lumens



D6B2-10W-27K-A
D6B2-10W-30K-A

10 Watts
550 Lumens



DIRECTIONAL



DIRECTIONAL

Brass Spot and Down Lights

IP65 Rated; Lifetime Warranty

LumienPRO
BY LUMIEN LIGHTING



D7B1-10W-A
10 Watts
550 Lumens
WW (2700-5000K)

LumienPRO
BY LUMIEN LIGHTING



D7B2-10W-A
10 Watts
480 Lumens
WW (2700-5000K)

LumienPRO
BY LUMIEN LIGHTING



D9B1-10W-A
10 Watts
XXX Lumens
RGBWW (2700K – 5000K)

LumienPRO
BY LUMIEN LIGHTING



D9B2-10W-A
10 Watts
XXX Lumens
RGBWW (2700K – 5000K)

DIRECTIONAL



DIRECTIONAL



Micro Brass Spot and Down Lights

IP65 Rated; Lifetime Warranty



LAB-068

60° Up Shroud
With Wired Knuckle
& LAP-002

Micro Module Ordered Separately



LAB-069

37° Down Shroud
With Wired Knuckle
& LAP-001

Micro Module Ordered Separately



M4B7-5.5W-27K-A
M4B7-5.5W-30K-A

5.5 Watts
275 Lumens

FLOOD



Brass Flood Lights

IP65 Rated; Lifetime Warranty



F6B1-5W-27K-A
F6B1-5W-30K-A

5 Watts
320 Lumens



F6B1-10W-27K-A
F6B1-10W-30K-A

10 Watts
500 Lumens

FLOOD

Brass Flood Lights

IP65 Rated; Lifetime Warranty

LumienPRO
BY LUMIEN LIGHTING



F7B1-10W-A
10 Watts
460 Lumens
WW (2700-5000K)

LumienPRO
BY LUMIEN LIGHTING



F9B1-10W-A
10 Watts
XXX Lumens
RGBWW (2700K – 5000K)



LAB-070
Flood Shroud
With Wired Knuckle
& LAP-002
Micro Module
Ordered Separately



WALL



Brass Wall Lights

IP65 Rated; Lifetime Warranty



W3B1-3.5W-27K-A

W3B1-3.5W-30K-A

2.5 Watts

170 Lumens



W4B4-2.5W-27K-A

W4B4-2.5W-30K-A

3.5 Watts

130 Lumens

WALL

Brass Wall Lights

IP65 Rated; Lifetime Warranty



W3B2-2.5W-27K-A
W3B2-2.5W-30K-A

2.5 Watts
170 Lumens
Twist & Lock Mount

LumienPRO
BY LUMIEN LIGHTING



W9B4-2.5W-A

2.5 Watts
XXX Lumens
RGBWW (2700K – 5000K)



UNDERWATER



Underwater Fixtures



M4B5-5.5W-27K-R
M4B5-5.5W-30K-R

5.5 Watts
346 Lumens



M4B6-5.5W-27K-R
M4B6-5.5W-30K-R

5.5 Watts
254 Lumens

BRASS ACCESSORIES

Mounting & Parts



LAB-001

Accessory, Brass Tree Mount, Single Point



LAB-002

Accessory, Brass Tree-Mount, Bracket



LAA-009

Accessory, Wall Light Surface Mount Bracket



LAB-058

Accessory, 4" Riser



LAB-051

Accessory, 8" Riser



LAB-052

Accessory, 16" Riser



LAB-053

Accessory, 24" Riser



LAB-049

Accessory, L-Mount



LAB-050

Accessory, T-Mount



LAB-037

Accessory, Threaded Cap for Brass Spot Light



LAB-066

Accessory, Brass Set Ring



LAB-016

Accessory, Micro Hexagon Louver



LAB-018

Micro, Accessory, Stake Attachment

BRASS ACCESSORIES

Micro Replacement Shrouds



LAB-031

Micro, Replacement
Shroud, 60° Uplight
Shroud Only



LAB-032

Micro, Replacement
Shroud, 37° Downlight
Shroud Only



LAB-033

Micro, Replacement
Shroud, 120° Spread Flood
Shroud Only



LAB-071

Micro, Shroud, 37 Degree
Downlight Shroud with
Extra Length Only



LAB-072

Micro, Shroud, Flood Shroud
with Extra Length Only

Path Light Components



LAP-001

Accessory, 12" Spike



LAP-002

Accessory, 8" Spike



LAP-005

Accessory, Commercial
16" Spike



LAS-002

Accessory, Stainless Steel
Trident Stake, 12"

BRASS ACCESSORIES

Micro Modules



M4B1-3.5W-27K-40-A
M4B1-3.5W-30K-40-A
M4B1-3.5W-27K-60-A
M4B1-3.5W-30K-60-A

3.5 Watts
325 Lumens
40° or 60° Options



M4B1-5.5W-27K-40-A
M4B1-5.5W-30K-40-A
M4B1-5.5W-27K-60-A
M4B1-5.5W-30K-60-A

5.5 Watts
435 Lumens
40° or 60° Options

LumienPRO
BY LUMIEN LIGHTING



M7B1-4.5W-40-A

4.5 Watts
350 Lumens
WW (2700K – 5000K)
40° Option



M8B1-3W-27K-40-A
M8B1-3W-30K-40-A

3 Watts
XXX Lumens
RGBW (2700K or 3000K)
40° Option

MISCELLANEOUS

LP-REMOTE

LumienPRO

Can be used with any LumienPRO fixture or LumienPRO module
Functionality is determined by fixture or module type



Transformers



TR -120
120 WATTS



TR -250
250 WATTS

GLOSSARY


Finishes Guide



Antique Brush
Brass



Raw
Brass



Bronze
Aluminum



Black
Aluminum

Abbreviation Key

BK - Black
BZ - Bronze
FT - Feet
K - Kelvin Temperature
LED - Light-emitting diode

LM - Lumens
R - Raw
TR - Transformer
V - Voltage
W - Wattage

Where To Buy



Scan to view
Distributor
Listing



Scan to follow
on facebook

Fixture Guide

Fixture Type	Fixture Components	Fixture Material	Fixture Style	Watts	Color Temperature	Finish
			<i>Depends on fixture category</i>	<i>Depends on fixture</i>		
D (Directional)	1 (Drop-In)	A (Aluminum)	1		27K (2700K)	BZ (Bronze) - Aluminum
A (Area)	2 (Modular)	B (Brass)	2		30K (3000K)	BK (Black - Available on Specific Fixtures) - Aluminum
F (Flood)	3 (Integrated Non-Modular)		3			Aluminum
W (Wall)	4 (Integrated Modular)		4			A (Antiqued) - Brass
R (Recessed)	5 (Integrated Variable)		5			R (Raw - Available on Specific Fixtures) - Brass
S (Step)	6 (Integrated Modular Variable)		6			
P (Pendant)	7 (LumienPRO WW – 2700-5000K)		7			
M (Micro)	8 (LumienPRO RGBW – Color + Defined CCT)		8			
N (Nano)						
Z (Macro)	9 (LumienPRO RGBWW – Color + 2700-5000K)					



WWW.LUMIENLIGHTING.COM

PH: 770.485.9002

