

BREATHABLE SURFACE PROTECTION SUITABLE FOR NEWLY INSTALLED FLOORS

PROTECTION FOR EVERYDAY PROJECTS

shielding from damage such as dust, dirt, moisture and spills.



LAMINATE • HARDWOOD • LUXURY VINYL PLANKS • TILE •
STAIRS • COUNTERTOPS AND MORE •

KEY FEATURES & ADVANTAGES

Self Adhesive | **anti slip • tackable**
Moisture Resistant | **protects against moisture**
Clean Removal | **damage free surfaces**
Impact Resistant | **cushions impact**
Quick Install | **no tape required**

PROTECTION FOR ALL PROJECTS

Construction
Moving
Remodeling
Drywall Install
Painting
Events/Parties
Temporary Protection

PLEASE NOTE.

The surface to be protected must remain dry, clean, dust-free, and free from chemical agents. It is advisable to conduct preliminary tests. Lay the rolls with an overlap of approximate 4" and press firmly. Processing temperature should be between 41° and 104° Fahrenheit. The breathable fleece allows up to 70 grams per m² per 24 hours. Not recommended for freshly laid porous or absorbent surfaces such as natural stone, clay tiles, and untreated concrete. The underfloor heating must be turned off. The surface to be covered must be free of any solvent vapors. No solvent vapors may be present on top of the areas to be covered.

Distributed by: **Pak-Lite, Inc. (PLI)**
134 PLI DRIVE
Commerce, Georgia 30529

www.quicprep.com
(800) 449-9459