



DATA SHEET



BREATHABLE SURFACE PROTECTION

10/2025

Made of breathable polyester fleece with an impermeable PE top layer and a self-adhesive underside. QuicPrep® Vapor Permeable Breathable Surface Protection is engineered for all hard and smooth floors such as laminate. Suitable for newly installed floors. QuicPrep® Vapor Permeable Breathable Surface Protection provides a shield for all projects against dust, moisture, dirt and accidental spills.

Product Specifications - Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

Material Use:	Temporary protection for completely dry surfaces
Breathable:	The fleece lets through 70 grams of air per m ² per 24 hours
Composition:	Top layer is blue PE film Middle layer is recycled polyester fleece Bottom layer is an temporary adhesive
Product Color:	Blue
Adhesive Type:	Acrylic
Adhesion Level:	Light tack
Available sizes:	39.37" x 82' ~ 269 square feet

Features and Benefits

- Cvacjjclra fmgac dmp qspdaacq rf_r lccb rm` reathe
- Anti-slip and tackable with self adhesive backing
- Protects against moisture
- Impact resistant
- No tape required
- Clean removal for damage free surfaces
- Reusable

Temporary Protection for All Projects

- Construction
- Moving
- Remodeling
- Drywall Install
- Painting
- Events / Parties

Application / Removal Techniques

The surface to be protected must remain dry, clean, dust-free, and free from chemical agents. It is advisable to conduct preliminary testing. Lay the rolls with an overlap of approximately 4 inches and press firmly. Application temperature should be between 41° and 104° Fahrenheit. The breathable fleece allows up to 70 grams of air per m² per 24 hours. **Not recommended** for use on newly installed surfaces including porous stones, natural stones, clay tiles, and recently laid concrete. The underfloor heating must be turned off. The surface to be covered must be free of any solvent vapors. No solvent vapors may be present on top of the areas to be covered. Durable for up to three months.

THIS DATA REPRESENTS TYPICAL VALUES OF NORMAL PRODUCTION MATERIAL. This is not offered as an exact product specification or guarantee, except that it is accurate to the best of Pak-Lite, Inc.'s knowledge or obtained from sources believed to be accurate. User must determine the sustainability of the product for end use.