



DATA SHEET



6 MIL MOISTURE BARRIER

10/2025

6 mil thick polyethylene film moisture barrier flooring underlayment for vinyl, laminate, and engineered hardwood flooring. QuicPrep® Moisture Barrier Flooring Underlayment film is designed to protect against harmful moisture vapors. It includes adhesive tape strip for DIY friendly installs.

Product Specifications - Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

Material Use:	Moisture barrier flooring underlayment LLDPE	
Material:	(Linear Low-Density Polyethylene)	
Film Color:	Black	
Total Thickness:	6 mils (0.15 mm)	
Water Vapor Emission	0.076 lbs./1,000 ft ² /24 hrs	
Tensile Strength:	MD 4,000 psi	TD 2,000 psi
Elongation:	MD 400%	TD 700%
Tear Strength:	MD 1,200 gf	TD 6,000 gf
Available sizes:	Multiple sizes available starting at 100 square feet at 46" wide	

Features and Benefits

- For use with vinyl, laminate, and engineered hardwood floors
- Limited lifetime warranty
- Helps protect floors against moisture vapors
- Proudly made in the USA
- Moisture barrier for concrete sub floors
- Easy to seal with adhesive tape strip - included

Installation

- Refer to the Installation Instructions published on the OsgaNpcnã website @ www.quicprep.com.

THIS DATA REPRESENTS TYPICAL VALUES OF NORMAL PRODUCTION MATERIAL. This is not offered as an exact product specification or guarantee, except that it is accurate to the best of Pak-Lite, Inc.'s knowledge or obtained from sources believed to be accurate. User must determine the sustainability of the product for end use.